



Zeagle Product Specifications

Zeagle Regulators

Envoy Features



Envoy-Yoke
1st and 2nd Stages
350-3110

ENVOY FIRST STAGE FEATURES:

- High Performance Porting
- Conical Precision HP valve
- Balanced Diaphragm
- Yoke or DIN inlet available
- 5 Low Pressure Ports (3/8"-24 UNF)
- 2 High Pressure Ports (7/16"-20 UNF)
- Weight 1.88 lb. (.89 kg.)
- Intermediate Pressure: 135-150 psi (9-10 bar)

First Stage Materials:

- Body: Brass
- O-rings: Buna-N
- Seat: Advanced Polymer
- HP Valve: Stainless Steel

ENVOY SECOND STAGE FEATURES:

- Downstream valve
- Balanced Diaphragm
- Dive/Pre Dive Venturi Control
- Weight: .42 lb. (.26 kg) (w/o hose)
- Hose Length: 30 in. (.76 m)

Second Stage Materials:

- Cover: Flexible Thermoplastic
- Case: Thermoplastic
- Poppet Seat: Elastomer
- O-Rings: Buna-N
- Diaphragm: Elastomeric Polymer
- Exhaust Valve: Elastomer
- Mouthpiece: Silicone

Envoy

(under \$300 price class):

"Zeagle's redesigned Envoy was the only reg in it's price class to earn perfect simulator scores, even at the most demanding RMV/ depth. It also delivered far and away the best in-water performance. An easy breather in all positions and extremely dry, the Envoy has a forceful purge and a dive/ pre dive lever that is very effective in controlling surface free flows. ...The Envoy offers the best warranty in it's price group"

-Rodale's Scuba Diving, Nov. 2003:
Best New Regs

Work of breathing at heavy demand: 1.05 Joule/Liter*
*198' (60M) depth, 750 psi inlet, 62.5 RMV (liters per minute respiratory volume)

Shipping Weight 3.25 LBS

